

according to Regulation (EC) No 1907/2006

Silikonspray

Print date: 20.06.2018 Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Silicone Spray

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

No information available.

1.3. Details of the supplier of the safety data sheet

Company name: WINKEL GmbH Street: Lisztstraße 1

Place: 53881 Euskirchen - Germany

Telephone: +49 2251 77 69 400-401 Telefax: Fax: +49 2251 77 69 402

e-mail: info@winkelgroup.de Internet: www.winkelgroup.de

1.4. Emergency telephone

number:

BfR Bundesinstitut für Risikobewertung: +49-30-18412-0

Ontario Poison Centre: +1 (800)-268-9017

Alberta Poison & Drug Information Service: +1 (800) 332-1414 American Association of Poison Control Centers: +1 (800) 222-1222

The Centre antipoison du Québec: +1 (800) 463-5060

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories: Aerosol: Aerosol 1

Aspiration hazard: Asp. Tox. 1 Skin corrosion/irritation: Skin Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3 Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated. May be fatal if swallowed and enters airways.

Causes skin irritation.

May cause drowsiness or dizziness.

Harmful to aquatic life with long lasting effects.



according to Regulation (EC) No 1907/2006

Silikonspray

Print date: 20.06.2018 Page 2 of 13

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

Hydrocarbons, C6-C7, n-alkanes, isoalkanes cyclic, < 5% n-hexane

Hydrocarbons, C7, n-alkanes, iso-alkanes, cyclics

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, <2% aromatics

2-Propanol

Signal word: Danger

Pictograms:





Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe Aerosol.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves.

P312 Call a POISON CENTER/doctor if you feel unwell.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container according to the official regulations.

Special labelling of certain mixtures

EUH208 Contains (R)-p-mentha-1,8-diene, d-limonene. May produce an allergic reaction.

2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

SECTION 3: Composition/information on ingredients

3.2. Mixtures



according to Regulation (EC) No 1907/2006

Silikonspray

Print date: 20.06.2018 Page 3 of 13

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to			
106-97-8	butane			25 - < 50 %
	203-448-7	601-004-00-0	01-2119474691-32	
	Flam. Gas 1, Liquefied ga	s; H220 H280	•	
75-28-5	isobutane			25 - < 50 %
	200-857-2	601-004-00-0	01-2119485395-27	
	Flam. Gas 1, Liquefied ga	s; H220 H280		
64742-49-0	Hydrocarbons, C6-C7, n-a	alkanes, isoalkanes cyclic, < 5% n-	hexane	10 - < 20 %
	921-024-6		01-2119475514-35	
	Flam. Liq. 2, Skin Irrit. 2, S H411	STOT SE 3, Asp. Tox. 1, Aquatic C	hronic 2; H225 H315 H336 H304	
64742-49-0	Hydrocarbons, C7, n-alka	10 - < 20 %		
	927-510-4		01-2119475515-33	
	Flam. Liq. 2, Skin Irrit. 2, S H411			
74-98-6	propane			3 - < 5 %
	200-827-9	601-003-00-5	01-2119486944-21	
	Flam. Gas 1, Liquefied ga			
64742-48-9	Hydrocarbons, C9-C10, n	1 - < 3 %		
	927-241-2		01-2119471843-32	
	Flam. Liq. 3, STOT SE 3,			
67-63-0	2-Propanol	1 - < 3 %		
	200-661-7	603-117-00-0	01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2, S			
5989-27-5	(R)-p-mentha-1,8-diene, d	I-limonene		< 0.1 %
	227-813-5		01-2119529223-47	
	Flam. Liq. 3, Skin Irrit. 2, 5 H315 H317 H304 H400 H	Skin Sens. 1, Asp. Tox. 1, Aquatic A 410	Acute 1, Aquatic Chronic 1; H226	

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

After inhalation

Remove person to fresh air and keep comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with skin

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue



according to Regulation (EC) No 1907/2006

Silikonspray

Print date: 20.06.2018 Page 4 of 13

rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

4.2. Most important symptoms and effects, both acute and delayed

Headache, nausea, dizziness, fatigue, skin irritation

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water fog. Foam. Carbon dioxide (CO2). Extinguishing powder.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO2, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

Additional information

Danger of bursting container.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Wear personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Observe instructions for use.

Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

When using do not eat, drink, smoke, sniff.

Wear personal protection equipment (refer to section 8).



according to Regulation (EC) No 1907/2006

Silikonspray

Print date: 20.06.2018 Page 5 of 13

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Heating causes rise in pressure with risk of bursting.

Further information on handling

Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Observe legal regulations and provisions.

Advice on storage compatibility

Do not store together with: Oxidizing agents. Pyrophoric or self-heating substances. Food and feedingstuffs.

Further information on storage conditions

Protect from frost. Protect against direct sunlight. Store in a cool dry place. Observe legal regulations and provisions.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance				
DNEL type		Exposure route	Effect	Value	
64742-48-9	4742-48-9 Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, <2% aromatics				
Worker DNEL, long-term inhalation s			systemic	871 mg/m³	
Worker DNEL,	long-term	dermal	systemic	77 mg/kg bw/day	
Consumer DNE	EL, long-term	inhalation	systemic	185 mg/m³	
Consumer DNEL, long-term		dermal	systemic	46 mg/kg bw/day	
Consumer DNEL, long-term		oral	systemic	46 mg/kg bw/day	

Additional advice on limit values

a no restriction

b End of exposure or end of shift

c at long term exposure: after several previous shifts

d before next shift

blood (B)

Urine (U)

8.2. Exposure controls

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used.



according to Regulation (EC) No 1907/2006

Silikonspray

Print date: 20.06.2018 Page 6 of 13

Protective and hygiene measures

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

Eye/face protection

Suitable eye protection: Tightly sealed safety glasses.

DIN EN 166

Hand protection

Protect skin by using skin protective cream. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber) Breakthrough time (maximum wearing time) 480min

Thickness of the glove material 0,45 mm

DIN EN 374

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

When exceeding the relevant workplace exposure limits, note the following:

Suitable respiratory protective equipment: Combination filter device (DIN EN 141)...

Filtering device with filter or ventilator filtering device of type: AX

Observe the wear time limits as specified by the manufacturer.

Observe legal regulations and provisions.

Environmental exposure controls

Observe legal regulations and provisions.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Aerosol
Colour: colourless
Odour: Lemon

Test method

pH-Value (at 20 °C): No information available. DIN 19268

Changes in the physical state

Melting point:
Initial boiling point and boiling range:
-11,7 °C
Flash point:
-80 °C
Lower explosion limits:
1,1
Upper explosion limits:
9,4

Vapour pressure:No information available.Vapour pressure:No information available.

Density (at 20 °C): 0,7475 g/cm³ DIN 51757

Bulk density: not applicable
Partition coefficient: No information available.
Viscosity / dynamic: No information available.
Viscosity / kinematic: < 7 mm²/s
Flow time: not applicable



Revision date: 05.10.2017

according to Regulation (EC) No 1907/2006

Silikonspray

Print date: 20.06.2018 Page 7 of 13

Vapour density:

No information available.

9.2. Other information

Data apply to technical substance: Relative density, Colour, Odour, Viscosity, pH.

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

Do not expose to temperatures above 50 °C. Heating causes rise in pressure with risk of bursting.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Take precautionary measures against static discharges.

10.5. Incompatible materials

Oxidizing agents. Pyrophoric or self-heating substances.

10.6. Hazardous decomposition products

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO2, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

Further information

Do not mix with other chemicals.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicocinetics, metabolism and distribution

There are no data available on the mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.



according to Regulation (EC) No 1907/2006

Silikonspray

Print date: 20.06.2018 Page 8 of 13

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	
106-97-8	butane					
	inhalation (4 h) gas	LC50	658 ppm	Rat	GESTIS	
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes cyclic, < 5% n-hexane					
	oral	LD50	> 5000 mg/kg	Rat		
	dermal	LD50	> 2000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50	> 23,3 mg/l	Rat		
64742-49-0	Hydrocarbons, C7, n-alkanes, iso-al	kanes, cycli	cs			
	oral	LD50	5500 mg/kg	Rat		
	dermal	LD50	2770 mg/kg	Rat		
	inhalation (4 h) vapour	LC50	23,3 mg/l	Rat		
64742-48-9	Hydrocarbons, C9-C10, n-alkanes, i	soalkanes, o	cyclenes, <2% ard	omatics		
	oral	LD50 mg/kg	> 15000	Rat	Study report (1977)	
	dermal	LD50	> 5000 mg/kg	Rabbit	Study report (1993)	
	inhalation (4 h) vapour	LC50	> 4951 mg/l	Rat		
67-63-0	2-Propanol					
	oral	LD50	5280 mg/kg	Rat		
	dermal	LD50	> 2000 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50	47,5 mg/l	Rat		
5989-27-5	(R)-p-mentha-1,8-diene, d-limonene					
	oral	LD50	> 2000 mg/kg	Rat	Study report (2010)	
	dermal	LD50	> 2000 mg/kg	Kaninchen	IUCLID	

Irritation and corrosivity

Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Contains (R)-p-mentha-1,8-diene, d-limonene. May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

No indication of human carcinogenicity.

No indications of human germ cell mutagenicity exist.

No indications of human reproductive toxicity exist.

STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C6-C7, n-alkanes, isoalkanes cyclic, < 5% n-hexane; Hydrocarbons, C7, n-alkanes, iso-alkanes, cyclics)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No information available.

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].



according to Regulation (EC) No 1907/2006

Silikonspray

Print date: 20.06.2018 Page 9 of 13

SECTION 12: Ecological information

12.1. Toxicity

There are no data available on the mixture itself.

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h] [d]	Species	Source		
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes cyclic, < 5% n-hexane							
	Acute fish toxicity	LC50	> 1-10 mg/l	96 h	Pimephales promelas			
	Acute algae toxicity	ErC50 mg/l	> 10 - 100	72 h	Pseudokirchneriella subcapitata			
	Acute crustacea toxicity	EC50	> 1-10 mg/l	48 h	Daphnia magna			
64742-49-0	Hydrocarbons, C7, n-alkanes,	iso-alkanes,	cyclics					
	Acute fish toxicity	LC50	>1 - 10 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)			
	Acute algae toxicity	ErC50 mg/l	>10 - 100	72 h	Algae toxicity			
	Acute crustacea toxicity	EC50	>1 - 10 mg/l	48 h	Daphnia magna			
64742-48-9	Hydrocarbons, C9-C10, n-alka	nes, isoalkar	nes, cyclenes, <2º	% aromat	tics			
	Acute fish toxicity	LC50	>1000 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)			
	Acute algae toxicity	ErC50	>1000 mg/l	72 h	Pseudokirchneriella subcapitata			
	Acute crustacea toxicity	EC50	>1000 mg/l	48 h	Daphnia magna			
	Fish toxicity	NOEC	0,182 mg/l	28 d	Oncorhynchus mykiss	CONCAWE, Brussels, Belgium (2010)		
	Crustacea toxicity	NOEC	0,317 mg/l	21 d	Daphnia magna	Company report (2010)		
67-63-0	2-Propanol							
	Acute fish toxicity	LC50	9640 mg/l	96 h	Pimephales promelas			
	Acute algae toxicity	ErC50	> 100 mg/l	72 h	Desmodesmus subspicatus			
	Acute crustacea toxicity	EC50	> 100 mg/l	48 h	Daphnia magna			
5989-27-5	(R)-p-mentha-1,8-diene, d-limo	nene						
	Acute fish toxicity	LC50	0,72 mg/l	96 h	Pimephales promelas	Study report (1990)		
	Acute algae toxicity	ErC50	0,32 mg/l	72 h	Pseudokirchneriella subcapitata	Study report (2013)		
	Acute crustacea toxicity	EC50	0,307 mg/l	48 h	Daphnia magna	Study report (2013)		
	Fish toxicity	NOEC	0,37 mg/l	8 d	Pimephales promelas	Study report (2015)		
	Crustacea toxicity	NOEC	0,08 mg/l	21 d	Daphnia magna	Study report (2016)		
	Acute bacteria toxicity	(209 mg/	/I)	3 h	activated sludge of a predominantly domestic sewag	Study report (2010)		

12.2. Persistence and degradability

There are no data available on the mixture itself. AOX (mg/l): 0



according to Regulation (EC) No 1907/2006

Silikonspray

Print date: 20.06.2018

Page 10 of 13

CAS No	Chemical name				
	Method	Value	d	Source	
	Evaluation				
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes cyclic, < 5% n-hexane				
	OECD Guideline 301 F 98% 28				
	Easily biodegradable (concerning to the criteria of the OECD)				

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
106-97-8	butane	2,89
75-28-5	isobutane	2,8
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes cyclic, < 5% n-hexane	3,4 - 5,2
74-98-6	propane	2,36
67-63-0	2-Propanol	0,05
5989-27-5	(R)-p-mentha-1,8-diene, d-limonene	4,38

BCF

CAS No	Chemical name	BCF	Species	Source
	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, <2% aromatics	144,3	calculated	Other company data (
5989-27-5	(R)-p-mentha-1,8-diene, d-limonene	908,5		Other company data (

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

Waste disposal number of waste from residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

Waste disposal number of used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

Waste disposal number of contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately

collected municipal packaging waste); metallic packaging

SECTION 14: Transport information



according to Regulation (EC) No 1907/2006

Silikonspray

Print date: 20.06.2018 Page 11 of 13

Land transport (ADR/RID)

14.1. UN number: UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1Classification code:5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Excepted quantity: E0
Transport category: 2
Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1Classification code:5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number: UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1Marine pollutant:no

Special Provisions: 63, 190, 277, 327, 344, 381,959

Limited quantity: 1000 mL Excepted quantity: E0 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1950

14.2. UN proper shipping name: AEROSOLS, flammable

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1

Special Provisions: A145 A167 A802

Limited quantity Passenger: 30 kg G
Passenger LQ: Y203
Excepted quantity: E0

IATA-packing instructions - Passenger:203IATA-max. quantity - Passenger:75 kgIATA-packing instructions - Cargo:203IATA-max. quantity - Cargo:150 kg

14.5. Environmental hazards



according to Regulation (EC) No 1907/2006

Silikonspray

Print date: 20.06.2018 Page 12 of 13

ENVIRONMENTALLY HAZARDOUS: no

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 28: butane; isobutane; Hydrocarbons, C6-C7, n-alkanes, isoalkanes cyclic, < 5% n-hexane;

Hydrocarbons, C7, n-alkanes, iso-alkanes, cyclics; Hydrocarbons, C9-C10, n-alkanes, iso-alkanes, cyclenes,

<2% aromatics

2010/75/EU (VOC): No information available. 2004/42/EC (VOC): No information available.

Additional information

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]:

Calculation method.

Aerosol directive (75/324/EEC)

National regulatory information

Water contaminating class (D): 1 - slightly water contaminating

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,3,6,8,9,11,14,15.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA: International Air Transport Association

IMDG: International Maritime Code for Dangerous Goods

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL/DMEL: Derived No Effect Level / Derived Minimal Effect Level

WEL (UK): Workplace Exposure Limits

TWA (EC): Time-Weighted Average

ATE: Acute Toxicity Estimate

STEL (EC) Short Term Exposure Limit

LC50: Lethal Concentration

EC50: half maximal Effective Concentration

ErC50: means EC50 in terms of reduction of growth rate

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.

H229 Pressurised container: May burst if heated.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.





according to Regulation (EC) No 1907/2006

Print date: 20.06.2018	Silikonspray	Page 13 of 13
H317	May cause an allergic skin reaction.	
H319	Causes serious eye irritation.	
H336	May cause drowsiness or dizziness.	
H400	Very toxic to aquatic life.	
H410	Very toxic to aquatic life with long lasting effects.	
H411	Toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	
EUH066	Repeated exposure may cause skin dryness or cracking.	
EUH208	Contains (R)-p-mentha-1,8-diene, d-limonene. May produce an allergic reaction.	
Further Information		

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)