



Revision date: 05.12.2017

according to Regulation (EC) No 1907/2006

## **MULTI SIGNUM SPRAY**

Print date: 20.06.2018 Page 1 of 11

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

# 1.1. Product identifier

**MULTI SIGNUM SPRAY** 

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Lubricant

### 1.3. Details of the supplier of the safety data sheet

Company name: WINKEL GmbH Street: Lisztstraße 1

Place: 53881 Euskirchen - Germany

Telephone: +49 2251 77 69 400-401 Telefax: +49 2251 77 69 402

e-mail: info@winkelgroup.de
Internet: www.winkelgroup.de

1.4. Emergency telephone Ontario Poison Centre: +1 (800)-268-9017

number: Alberta Poison & Drug Information Service: +1 (800) 332-1414

American Association of Poison Control Centers: +1 (800) 222-1222

### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

### Regulation (EC) No. 1272/2008

Hazard categories: Aerosol: Aerosol 1

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated. May cause drowsiness or dizziness.

### 2.2. Label elements

### Regulation (EC) No. 1272/2008

## Hazard components for labelling

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, <2% aromatics

Signal word: Danger

Pictograms:





## **Hazard statements**

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.
H336 May cause drowsiness or dizziness.

## **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

GB - EN

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.





### **MULTI SIGNUM SPRAY**

Print date: 20.06.2018 Page 2 of 11

P271 Use only outdoors or in a well-ventilated area.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container according to the official regulations.

### Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH208 Contains Benzenesulfonic acids, di-C10-14-alkyl derivatives, calcium salts. May produce

an allergic reaction.

#### 2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

## **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

#### Hazardous components

| CAS No       | Chemical name                    | Quantity                      |                  |               |
|--------------|----------------------------------|-------------------------------|------------------|---------------|
|              | EC No                            | Index No                      | REACH No         |               |
|              | Classification according to Regu | lation (EC) No. 1272/2008 [C  | LP]              |               |
| 75-28-5      | isobutane                        |                               |                  | 50 - <= 100 % |
|              | 200-857-2                        | 601-004-00-0                  | 01-2119485395-27 |               |
|              | Flam. Gas 1, Liquefied gas; H22  | 20 H280                       | •                |               |
| 64742-48-9   | Hydrocarbons, C9-C10, n-alkan    | es, isoalkanes, cyclenes, <2% | aromatics        | 20 - < 25 %   |
|              | 927-241-2                        |                               | 01-2119471843-32 |               |
|              | Flam. Liq. 3, STOT SE 3, Asp. 7  |                               |                  |               |
| 74-98-6      | propane                          | 5 - < 10 %                    |                  |               |
|              | 200-827-9                        | 601-003-00-5                  | 01-2119486944-21 |               |
|              | Flam. Gas 1, Liquefied gas; H22  |                               |                  |               |
| 106-97-8     | butane                           | 1 - < 3 %                     |                  |               |
|              | 203-448-7                        | 601-004-00-0                  | 01-2119474691-32 |               |
|              | Flam. Gas 1, Liquefied gas; H22  |                               |                  |               |
| 1471316-72-9 | Benzenesulfonic acids, di-C10-1  | < 0.1 %                       |                  |               |
|              | 939-603-7                        |                               | 01-2119978241-36 |               |
|              | Skin Sens. 1B; H317              |                               |                  |               |

Full text of H and EUH statements: see section 16.

### Labelling for contents according to Regulation (EC) No 648/2004

>= 30 % aliphatic hydrocarbons, perfumes.

### **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

#### **General information**

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

#### After inhalation

Remove person to fresh air and keep comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.



according to Regulation (EC) No 1907/2006

## **MULTI SIGNUM SPRAY**

Print date: 20.06.2018 Page 3 of 11

#### After contact with skin

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse . In all cases of doubt, or when symptoms persist, seek medical advice.

### After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

#### After ingestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

### 4.2. Most important symptoms and effects, both acute and delayed

Headache, nausea, dizziness, fatigue, skin irritation

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

#### Suitable extinguishing media

Water fog. Foam. Carbon dioxide (CO2). Extinguishing powder.

### Unsuitable extinguishing media

Full water jet

### 5.2. Special hazards arising from the substance or mixture

Incomplete combustion and thermolysis gases of different toxicity can occur . In the case of hydrocarbonaceous products such as CO, CO2, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

#### 5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

## Additional information

Danger of bursting container.

## **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear personal protection equipment.

## 6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

#### 6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

### **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling



according to Regulation (EC) No 1907/2006

### **MULTI SIGNUM SPRAY**

Print date: 20.06.2018 Page 4 of 11

#### Advice on safe handling

Observe instructions for use.

Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

When using do not eat, drink, smoke, sniff.

Wear personal protection equipment (refer to section 8).

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Heating causes rise in pressure with risk of bursting.

### Further information on handling

Avoid contact with skin and eyes.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed. Observe legal regulations and provisions.

## Advice on storage compatibility

Do not store together with: Oxidizing agents. Pyrophoric or self-heating substances. Food and feedingstuffs.

#### Further information on storage conditions

Protect from frost. Protect against direct sunlight. Store in a cool dry place. Observe legal regulations and provisions.

### 7.3. Specific enduse(s)

No information available.

## **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

#### **Exposure limits (EH40)**

| CAS No   | Substance | ppm | mg/m³ | fibres/ml | Category      | Origin |
|----------|-----------|-----|-------|-----------|---------------|--------|
| 106-97-8 | Butane    | 600 | 1450  |           | TWA (8 h)     | WEL    |
|          |           | 750 | 1810  |           | STEL (15 min) | WEL    |

#### **DNEL/DMEL values**

| CAS No                   | Substance  |                |          |                 |  |
|--------------------------|--|----------------|----------|-----------------|--|
| DNEL type                |  | Exposure route | Effect   | Value           |  |
| 64742-48-9               | Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, <2% aromatics |                |          |                 |  |
| Worker DNEL, long-term   |  | inhalation     | systemic | 871 mg/m³       |  |
| Worker DNEL, long-term   |  | dermal         | systemic | 77 mg/kg bw/day |  |
| Consumer DNEL, long-term |  | inhalation     | systemic | 185 mg/m³       |  |
| Consumer DNEL, long-term |  | dermal         | systemic | 46 mg/kg bw/day |  |
| Consumer DNEL, long-term |  | oral           | systemic | 46 mg/kg bw/day |  |

### Additional advice on limit values

a no restriction

b End of exposure or end of shift

c at long term exposure: after several previous shifts

d before next shift

blood (B)





### **MULTI SIGNUM SPRAY**

Print date: 20.06.2018 Page 5 of 11

Urine (U)

#### 8.2. Exposure controls

### Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used.

#### Protective and hygiene measures

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

#### Eye/face protection

Suitable eye protection: Tightly sealed safety glasses.

**DIN EN 166** 

#### Hand protection

Protect skin by using skin protective cream. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber) Breakthrough time (maximum wearing time) 480min

Thickness of the glove material 0,45 mm

**DIN EN 374** 

### **Skin protection**

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.

#### Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

When exceeding the relevant workplace exposure limits, note the following:

Suitable respiratory protective equipment: Combination filter device (DIN EN 141)...

Filtering device with filter or ventilator filtering device of type: AX

Observe the wear time limits as specified by the manufacturer.

Observe legal regulations and provisions.

### **Environmental exposure controls**

Observe legal regulations and provisions.

## **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state: Aerosol
Colour: brown
Odour: sweetish

**Test method** 

pH-Value (at 20 °C): not determined DIN 19268

Changes in the physical state

Melting point: not determined Initial boiling point and boiling range:  $-42 \, ^{\circ}\text{C}$  Flash point:  $-80 \, ^{\circ}\text{C}$ 

Flammability

Solid: not applicable
Gas: not applicable
Lower explosion limits: 0,6
Upper explosion limits: 9,4

**Auto-ignition temperature** 

Solid: not applicable



according to Regulation (EC) No 1907/2006

### **MULTI SIGNUM SPRAY**

Print date: 20.06.2018 Page 6 of 11

Gas: not applicable

Decomposition temperature: not determined

**Oxidizing properties** 

Not oxidising.

Vapour pressure: not determined Vapour pressure: No information available.

Density (at 20 °C): 0,783 g/cm³ DIN 51757

Bulk density: not applicable

Water solubility:

The study does not need to be conducted because the substance is known to be

insoluble in water.

Solubility in other solvents

not determined

Partition coefficient:

Viscosity / dynamic:

No information available.

Viscosity / kinematic:

< 7 mm²/s

Flow time:

not applicable

Vapour density:

not determined

Evaporation rate:

not determined

9.2. Other information

Solid content: not determined

Data apply to technical substance: Relative density, Colour, Odour, Viscosity, pH.

### **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

#### 10.2. Chemical stability

The product is stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Do not expose to temperatures above 50 °C. Heating causes rise in pressure with risk of bursting.

#### 10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Take precautionary measures against static discharges.

### 10.5. Incompatible materials

Oxidizing agents. Pyrophoric or self-heating substances.

#### 10.6. Hazardous decomposition products

Incomplete combustion and thermolysis gases of different toxicity can occur . In the case of hydrocarbonaceous products such as CO, CO2, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

#### **Further information**

Do not mix with other chemicals.

### **SECTION 11: Toxicological information**

## 11.1. Information on toxicological effects



according to Regulation (EC) No 1907/2006

### **MULTI SIGNUM SPRAY**

Print date: 20.06.2018 Page 7 of 11

### Toxicocinetics, metabolism and distribution

There are no data available on the mixture itself.

### **Acute toxicity**

Based on available data, the classification criteria are not met.

| CAS No           | Chemical name  |               |              |         |                     |
|------------------|--|---------------|--------------|---------|---------------------|
|                  | Exposure route   | Dose          |              | Species | Source              |
| 64742-48-9       | Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, <2% aromatics |               |              |         |                     |
|                  | oral   | LD50<br>mg/kg | > 15000      | Rat     | Study report (1977) |
|                  | dermal   | LD50          | > 5000 mg/kg | Rabbit  | Study report (1993) |
|                  | inhalation (4 h) vapour  | LC50          | > 4951 mg/l  | Rat     |                     |
| 106-97-8         | butane   |               |              |         |                     |
|                  | inhalation (4 h) gas   | LC50          | 658 ppm      | Rat     | GESTIS              |
| 1471316-72-<br>9 | Benzenesulfonic acids, di-C10-14-alkyl derivatives, calcium salts    |               |              |         |                     |
|                  | oral   | LD50          | > 5000 mg/kg | Rat     |                     |
|                  | dermal   | LD50          | > 5000 mg/kg | Rat     |                     |

### Irritation and corrosivity

Based on available data, the classification criteria are not met.

### Sensitising effects

Contains Benzenesulfonic acids, di-C10-14-alkyl derivatives, calcium salts. May produce an allergic reaction.

#### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

No indication of human carcinogenicity.

No indications of human germ cell mutagenicity exist.

No indications of human reproductive toxicity exist.

## STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, <2% aromatics)

## STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking.

### **Aspiration hazard**

Based on available data, the classification criteria are not met.

### Specific effects in experiment on an animal

No information available.

### Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

## **SECTION 12: Ecological information**

#### 12.1. Toxicity

The product is not: Ecotoxic.





## **MULTI SIGNUM SPRAY**

Print date: 20.06.2018 Page 8 of 11

| CAS No           | Chemical name  |          |            |             |  |                                      |  |  |
|------------------|--|----------|------------|-------------|--|--------------------------------------|--|--|
|                  | Aquatic toxicity   | Dose     |            | [h]   [d]   | Species                                | Source                               |  |  |
| 64742-48-9       | Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, <2% aromatics |          |            |             |  |                                      |  |  |
|                  | Acute fish toxicity  | LC50     | >1000 mg/l | 96 h        | Oncorhynchus mykiss<br>(Rainbow trout) |                                      |  |  |
|                  | Acute algae toxicity   | ErC50    | >1000 mg/l | 72 h        | Pseudokirchneriella<br>subcapitata     |                                      |  |  |
|                  | Acute crustacea toxicity   | EC50     | >1000 mg/l | 48 h        | Daphnia magna                          |                                      |  |  |
|                  | Fish toxicity  | NOEC     | 0,182 mg/l | 28 d        | Oncorhynchus mykiss                    | CONCAWE, Brussels,<br>Belgium (2010) |  |  |
|                  | Crustacea toxicity   | NOEC     | 0,317 mg/l | 21 d        | Daphnia magna                          | Company report (2010)                |  |  |
| 1471316-72-<br>9 | Benzenesulfonic acids, di-C10-14-alkyl derivatives, calcium salts    |          |            |             |  |                                      |  |  |
|                  | Acute fish toxicity  | LC50     | > 100 mg/l | 96 h        | Oncorhynchus mykiss<br>(Rainbow trout) |                                      |  |  |
|                  | Acute algae toxicity   | ErC50    | > 100 mg/l | <b>72</b> h | Pseudokirchneriella<br>subcapitata     |                                      |  |  |
|                  | Acute crustacea toxicity   | EC50     | > 100 mg/l | 48 h        | Daphnia magna (Big water flea)         |                                      |  |  |
|                  | Acute bacteria toxicity  | (> 10000 | 0 mg/l)    |             |  | OECD-209                             |  |  |

## 12.2. Persistence and degradability

The product has not been tested.

## 12.3. Bioaccumulative potential

The product has not been tested.

### Partition coefficient n-octanol/water

| CAS No   | Chemical name | Log Pow |
|----------|---------------|---------|
| 75-28-5  | isobutane     | 2,8     |
| 74-98-6  | propane       | 2,36    |
| 106-97-8 | butane        | 2,89    |

### BCF

| _          |                                     |       |            |                      |
|------------|-------------------------------------|-------|------------|----------------------|
| CAS No     | Chemical name                       | BCF   | Species    | Source               |
| 64742-48-9 | Hydrocarbons, C9-C10, n-alkanes,    | 144,3 | calculated | Other company data ( |
|            | isoalkanes, cyclenes, <2% aromatics |       |            |                      |

# 12.4. Mobility in soil

The product has not been tested.

### 12.5. Results of PBT and vPvB assessment

The product has not been tested.

## 12.6. Other adverse effects

No information available.

# Further information

Avoid release to the environment.

# **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

## Advice on disposal

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.





### **MULTI SIGNUM SPRAY**

Print date: 20.06.2018 Page 9 of 11

### Waste disposal number of waste from residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; gases in pressure containers (including halons) containing hazardous

substances; hazardous waste

### Waste disposal number of used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; gases in pressure containers (including halons) containing hazardous

substances; hazardous waste

### Waste disposal number of contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately

collected municipal packaging waste); metallic packaging

## **SECTION 14: Transport information**

### Land transport (ADR/RID)

14.1. UN number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1Classification code:5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Excepted quantity: E0
Transport category: 2
Tunnel restriction code: D

## Inland waterways transport (ADN)

14.1. UN number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1Classification code:5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L
Excepted quantity: E0

## Marine transport (IMDG)

14.1. UN number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1Marine pollutant:no

Special Provisions: 63, 190, 277, 327, 344, 381,959

Limited quantity: 1000 mL Excepted quantity: E0 EmS: F-D, S-U

### Air transport (ICAO-TI/IATA-DGR)





### **MULTI SIGNUM SPRAY**

Print date: 20.06.2018 Page 10 of 11

14.1. UN number: UN 1950

14.2. UN proper shipping name: AEROSOLS, flammable

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1

Special Provisions: A145 A167 A802

Limited quantity Passenger: 30 kg G
Passenger LQ: Y203
Excepted quantity: E0

IATA-packing instructions - Passenger:

IATA-max. quantity - Passenger:

IATA-packing instructions - Cargo:

IATA-max. quantity - Cargo:

150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

### 14.6. Special precautions for user

Warning: Flammable gases.

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

### **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 28: isobutane; Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, <2% aromatics; butane

2010/75/EU (VOC):

No information available.

No information available.

#### **Additional information**

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]:

Calculation method.

Aerosol directive (75/324/EEC)

# National regulatory information

Water contaminating class (D): 1 - slightly water contaminating

## **SECTION 16: Other information**

### Changes

This data sheet contains changes from the previous version in section(s): 2,3,11,14.

#### Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail )

IATA: International Air Transport Association

IMDG: International Maritime Code for Dangerous Goods

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances



Revision date: 05.12.2017

## **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

### **MULTI SIGNUM SPRAY**

Print date: 20.06.2018 Page 11 of 11

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL/DMEL: Derived No Effect Level / Derived Minimal Effect Level

WEL (UK): Workplace Exposure Limits TWA (EC): Time-Weighted Average ATE: Acute Toxicity Estimate

ATE. Acute Toxicity Estimate

STEL (EC) Short Term Exposure Limit

LC50: Lethal Concentration

EC50: half maximal Effective Concentration

ErC50: means EC50 in terms of reduction of growth rate

### Relevant H and EUH statements (number and full text)

| H220 | Extremely flammable gas.     |
|------|------------------------------|
| H222 | Extremely flammable aerosol. |
| H226 | Flammable liquid and vapour. |

H229 Pressurised container: May burst if heated.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H317 May cause an allergic skin reaction. H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH208 Contains Benzenesulfonic acids, di-C10-14-alkyl derivatives, calcium salts. May produce

an allergic reaction.

#### **Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)